

Contact Interface

Product ref.: 153149A0



Product features

- Small contact interface for integration e.g. of conventional glass break sensors or magnet contacts into the Homematic IP smart home system
- Reliable monitoring of windows or doors in conjunction with connected contacts via the Homematic IP smartphone app – also while being away from home
- Long battery lifetime of up to 4 years and stand-alone operation possible without connection to the power supply
- Easy connection to a glass break sensor or magnetic contact via a two-wire cable
- Comfortable connection via screwless terminals
- Wireless operation and battery operation allow for flexible and easy installation to walls or window/door frames using the supplied mounting material
- To enable operation, the device has to be connected with one of the following solutions:
 - Homematic IP Access Point with free smartphone app and free cloud service
 - Central Control Unit CCU2/CCU3 with local user interface WebUI
 - Third-party solutions of partners

Technical specifications

Supply voltage	2x 1.5 V LR03/micro/AAA
Battery life	4 years (typ.)
Degree of protection	IP20
Ambient temperature	5 to 35 °C
Dimensions (W x H x D)	26 x 100 x 17 mm
Weight	30 g (including batteries)
Radio frequency band	868.0-868.6 MHz 869.4-869.65 MHz
Typ. open area RF range	330 m

Logistical data

Product reference	153149A0
EAN code	4047976531493
Short description	HmIP-SCI
Packing unit	144
Packing dimensions	122 x 93 x 36 mm
Weight incl. packaging	113.6 g

Package contents

Homematic IP Contact Interface
1.5 V LR03/micro/AAA batteries (2x)
Mounting material (2x adhesive strips, 2x screws and 2x plugs)
User manual